

A Tm:YAG laser

THIS INVENTION relates to a Tm:YAG laser, and in particular to a high power room-temperature Tm:YAG laser.

Thulium-doped Yttrium-Aluminium-Garnet (Tm:YAG) lasers comprise a sample of Tm:YAG, which is typically provided in the form of a rod. Adjacent the rod, a source of energy is provided to "pump" the Tm:YAG, in order to populate the excited 3F_4 electronic state of the Tm^{3+} ions contained within the Tm:YAG rod. It is the stimulated emission transition of Tm^{3+} ions between the 3F_4 state and the 3H_6 state that produces photons of the desired wavelength, namely $2.02\mu m$, to form the laser beam.

Two mirrors are provided, one at either end of the Tm:YAG rod. Both of the mirrors are highly reflective to radiation having a wavelength in the region of $2\mu m$. Hence, photons having wavelengths of $2.02\mu m$ produced in the Tm:YAG rod are reflected back and forth between the mirrors and repeatedly through the Tm:YAG rod. It will be understood that the mirrors and the Tm:YAG sample constitute a resonant cavity.

One of the mirrors is typically constructed to have almost total reflectivity at $2\mu m$ (for instance, 99.9% reflectivity), and the other of the mirrors is constructed to have a slightly lower reflectivity (for instance, 75-95% reflectivity). Hence, a portion of the $2.02\mu m$ photons are allowed to escape from the resonant cavity through the mirror with the lower reflectivity. These escaping photons, which are collimated and coherent with one another, constitute the beam produced by the Tm:YAG laser.

Although the Tm:YAG laser finds many applications in various fields of technology, conventional techniques for pumping Tm:YAG lasers are cumbersome and expensive. For instance, most Tm:YAG lasers are pumped using radiation having a wavelength corresponding to the 785nm absorption peak of the Tm^{3+} ions (corresponding to the ${}^3\text{H}_6 \rightarrow {}^3\text{H}_4$ electronic transition of Tm^{3+}). When pumping a Tm:YAG laser using radiation of this wavelength, it is conventional to provide arrays of appropriately-tuned laser diodes, positioned adjacent the Tm:YAG rod, to act as sources of the pumping radiation.

However, such arrays of high-power laser diodes are expensive, and technical difficulties have been encountered in arranging the arrays to pump the Tm:YAG rod sufficiently to result in a laser beam of useful intensity.

It is an object of the present invention to provide a Tm:YAG laser that alleviates at least some of the above drawbacks.

Accordingly, one aspect of the present invention provides a device for producing laser radiation having a wavelength of about $2\mu\text{m}$, the device comprising: a solid-state sample capable of producing lasing transitions corresponding to a wavelength of about $2\mu\text{m}$; and a source of pumping radiation having a wavelength of about $1\mu\text{m}$, the source being arranged so that at least some of the radiation produced thereby is absorbed by the solid-state sample, causing the solid-state sample to emit radiation having a wavelength of about $2\mu\text{m}$.

Advantageously, the solid-state sample is a Tm:YAG sample.

Preferably, the source of pumping radiation having a wavelength of about $1\mu\text{m}$ comprises a $1\mu\text{m}$ resonant cavity having the solid-state sample located substantially therein.

Conveniently, the resonant cavity comprises a Nd:YAG sample and a first pair of members that are substantially reflective to radiation having a wavelength of about $1\mu\text{m}$, the Nd:YAG sample being substantially interposed between the first pair of members.

Advantageously, the device comprises a source of pumping radiation for the Nd:YAG sample to stimulate the Nd:YAG sample to emit radiation having a wavelength of about $1\mu\text{m}$.

Preferably, the source of pumping radiation for the Nd:YAG sample comprises a plurality of arrays of laser diodes.

Alternatively, the source of pumping radiation for the Nd:YAG sample comprises a plurality of flashlamps.

Conveniently, the solid-state sample is substantially interposed between a second pair of members, at least one of which is substantially reflective to radiation having a wavelength of about $2\mu\text{m}$.

Advantageously, the second pair of members is located substantially within the source of radiation having a wavelength of about $1\mu\text{m}$.

Preferably, the device produces laser radiation having a wavelength of substantially $2.02\mu\text{m}$.

09845945-043001
FOUO

Conveniently, the source of radiation having a wavelength of about $1\mu\text{m}$ is a source of radiation having a wavelength of substantially $1.064\mu\text{m}$.

Another aspect of the present invention provides a method of producing laser radiation having a wavelength of about $2\mu\text{m}$, the method comprising the steps of: providing a solid-state sample capable of producing lasing transitions corresponding to a wavelength of about $2\mu\text{m}$; and emitting pumping radiation having a wavelength of about $1\mu\text{m}$ so that at least some of the radiation having a wavelength of about $1\mu\text{m}$ is absorbed by the solid-state sample, causing the solid-state sample to emit radiation having a wavelength of about $2\mu\text{m}$.

Advantageously, the step of providing a solid-state sample comprises the step of providing a Tm:YAG sample.

Preferably, the step of emitting pumping radiation having a wavelength of about $1\mu\text{m}$ comprises the step of providing a resonant cavity having the solid-state sample located substantially therein.

Conveniently, the step of providing a resonant cavity comprises the steps of: providing a Nd:YAG sample; and providing a first pair of members that are substantially reflective to radiation having a wavelength of about $1\mu\text{m}$, the Nd:YAG sample being substantially interposed between the first pair of members.

Advantageously, the method comprises the steps of: providing a source of pumping radiation for the Nd:YAG sample; and stimulating the Nd:YAG

09845945-043001

Figure 1 shows a schematic layout of a Tm:YAG laser embodying the present invention; and

Figure 2 shows a schematic diagram of electronic transitions within a sample of Tm:YAG for use in the Tm:YAG laser of Figure 1.

Turning firstly to Figure 1, a Tm:YAG laser 1 embodying the present invention comprises a Neodymium-doped Yttrium-Aluminium-Garnet (Nd:YAG) laser 2, having a Nd:YAG rod 3 and first and second mirrors 4, 5. Preferably, the Nd:YAG rod 3 has a diameter of 4mm and a length of 105mm, and is water-cooled. The Nd:YAG rod 3 is interposed between the first and second mirrors 4, 5, the first and second mirrors 4, 5 being located along the longitudinal axis of the Nd:YAG rod 3 and being arranged such that their reflective surfaces face toward the ends of the Nd:YAG rod 3.

The first mirror 4 is preferably substantially planar, and is located relatively close to a first end of the Nd:YAG rod 3. Advantageously, there is a gap in the region of 1cm between the first end of the Nd:YAG rod 3 and the first mirror. The second mirror 5 is located substantially further away from a second end of the Nd:YAG rod 3, and advantageously a gap of around 15cm is provided between these components. Preferably, the second mirror 5 is a concave mirror, having a radius of curvature of around 0.2m, with the concave mirror surface being directed toward the second end of the Nd:YAG rod 3.

A source of pumping radiation is provided for the Nd:YAG rod 3. This pumping source could, for example, be a simple flash-lamp arrangement but, in the present embodiment, preferably takes the form of a plurality of arrays 6 of laser diodes provided adjacent opposing sides of the Nd:YAG rod 3. Radiation

0945945-043001
T00E40"54654860

emitted by the diode laser arrays 6 is absorbed by the Nd:YAG rod 3 and the absorption of this radiation by the Nd:YAG rod 3 pumps the Nd:YAG rod 3, thereby causing the Nd:YAG rod 3 to generate photons having wavelengths of $1.064\mu\text{m}$. The first and second mirrors 4, 5 are substantially reflective to radiation having a wavelength of $1.064\mu\text{m}$, having reflectivities of around 95% and 99% respectively in this wavelength range.

It will be appreciated that the Nd:YAG rod 3 and the first and second mirrors 4, 5 form a resonant cavity, in which resonant waves of radiation of a wavelength of $1.064\mu\text{m}$ exist when the Nd:YAG laser 2 is active. As described above in relation to the Tm:YAG laser, a portion of the $1.064\mu\text{m}$ photons will escape from Nd:YAG laser 2 through the first mirror 4, forming the laser beam produced by the Nd:YAG laser 2.

Nd:YAG lasers are common and relatively inexpensive, and most laser laboratories have a Nd:YAG laser.

In the space provided between the second end of the Nd:YAG rod 3 and the second mirror 5, a rod 7 of Tm:YAG is provided. Preferably, the rod 7 of Tm:YAG is 105mm long, comprises around 2%-doped Tm:YAG, and is directly water-cooled within an O-ring sealed-flow tube, the coolant temperature being in the region of $16-18^{\circ}\text{C}$. The Tm:YAG rod 7 is substantially coaxially aligned with the Nd:YAG rod 3. Located between the second end of the Nd:YAG rod 3 and the Tm:YAG rod 7 is a third mirror 8. The third mirror 8 is preferably substantially planar, and is almost totally transmissive to radiation having a wavelength in the region of $1\mu\text{m}$, but almost totally reflective to radiation having a wavelength in the region $2\mu\text{m}$.

Located between the Tm:YAG rod 7 and the second mirror 5 is a fourth mirror 9, which is also preferably substantially planar, is almost totally transmissive to transmissive to radiation having a wavelength in the region of $1\mu\text{m}$, and is substantially reflective (although less reflective than the third mirror 8) to radiation having a wavelength in the region of $2\mu\text{m}$. The reflectivity of the fourth mirror 9 to radiation having a wavelength in the region of $2\mu\text{m}$ is lower than that of the fourth mirror, and in a preferred embodiment of the present invention is between around 75% and around 95%.

In use of the Tm:YAG laser 1, the arrays 6 of laser diodes in the Nd:YAG laser 2 cause, as discussed above, the Nd:YAG rod 3 to emit coherent photons having a wavelength of $1.064\mu\text{m}$, which form resonant waves in the resonant cavity in the space between the first and second mirrors 4, 5.

The absorption of radiation having a wavelength in the region of $1\mu\text{m}$ by Tm:YAG is relatively low, and is in the region of 0.0078 cm^{-1} . For this reason, it has been conventionally believed that radiation of this wavelength is unsuitable for pumping Tm:YAG lasers, since the majority of photons having a wavelength of around $1\mu\text{m}$ pass unabsorbed through the Tm:YAG rod of the Tm:YAG laser during a single pass.

However, due to the fact that the Tm:YAG rod 7 of the Tm:YAG laser 1 embodying the present invention is placed inside the resonant cavity of the Nd:YAG laser 2, the $1.064\mu\text{m}$ photons that exist in the resonant cavity of the Nd:YAG laser 2 pass through the Tm:YAG rod 7 many times. Hence, it will be understood that, when the Nd:YAG laser 2 produces high intra-cavity densities of $1.064\mu\text{m}$ photons in the resonant cavity between the first and second mirrors 4, 5, a large number of the photons will be absorbed by the Tm:YAG rod 7.

TOP SECRET

[illegible][illegible]

	1987	1986	1985	1984	1983	1982	1981	1980	1979	1978	1977	1976	1975	1974	1973	1972	1971	1970	1969	1968	1967	1966	1965	1964	1963	1962	1961	1960	1959	1958	1957	1956	1955	1954	1953	1952	1951	1950	1949	1948	1947	1946	1945	1944	1943	1942	1941	1940	1939	1938	1937	1936	1935	1934	1933	1932	1931	1930	1929	1928	1927	1926	1925	1924	1923	1922	1921	1920	1919	1918	1917	1916	1915	1914	1913	1912	1911	1910	1909	1908	1907	1906	1905	1904	1903	1902	1901	1900	1899	1898	1897	1896	1895	1894	1893	1892	1891	1890	1889	1888	1887	1886	1885	1884	1883	1882	1881	1880	1879	1878	1877	1876	1875	1874	1873	1872	1871	1870	1869	1868	1867	1866	1865	1864	1863	1862	1861	1860	1859	1858	1857	1856	1855	1854	1853	1852	1851	1850	1849	1848	1847	1846	1845	1844	1843	1842	1841	1840	1839	1838	1837	1836	1835	1834	1833	1832	1831	1830	1829	1828	1827	1826	1825	1824	1823	1822	1821	1820	1819	1818	1817	1816	1815	1814	1813	1812	1811	1810	1809	1808	1807	1806	1805	1804	1803	1802	1801	1800	1799	1798	1797	1796	1795	1794	1793	1792	1791	1790	1789	1788	1787	1786	1785	1784	1783	1782	1781	1780	1779	1778	1777	1776	1775	1774	1773	1772	1771	1770	1769	1768	1767	1766	1765	1764	1763	1762	1761	1760	1759	1758	1757	1756	1755	1754	1753	1752	1751	1750	1749	1748	1747	1746	1745	1744	1743	1742	1741	1740	1739	1738	1737	1736	1735	1734	1733	1732	1731	1730	1729	1728	1727	1726	1725	1724	1723	1722	1721	1720	1719	1718	1717	1716	1715	1714	1713	1712	1711	1710	1709	1708	1707	1706	1705	1704	1703	1702	1701	1700	1699	1698	1697	1696	1695	1694	1693	1692	1691	1690	1689	1688	1687	1686	1685	1684	1683	1682	1681	1680	1679	1678	1677	1676	1675	1674	1673	1672	1671	1670	1669	1668	1667	1666	1665	1664	1663	1662	1661	1660	1659	1658	1657	1656	1655	1654	1653	1652	1651	1650	1649	1648	1647	1646	1645	1644	1643	1642	1641	1640	1639	1638	1637	1636	1635	1634	1633	1632	1631	1630	1629	1628	1627	1626	1625	1624	1623	1622	1621	1620	1619	1618	1617	1616	1615	1614	1613	1612	1611	1610	1609	1608	1607	1606	1605	1604	1603	1602	1601	1600	1599	1598	1597	1596	1595	1594	1593	1592	1591	1590	1589	1588	1587	1586	1585	1584	1583	1582	1581	1580	1579	1578	1577	1576	1575	1574	1573	1572	1571	1570	1569	1568	1567	1566	1565	1564	1563	1562	1561	1560	1559	1558	1557	1556	1555	1554	1553	1552	1551	1550	1549	1548	1547	1546	1545	1544	1543	1542	1541	1540	1539	1538	1537	1536	1535	1534</
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	--------

[illegible]

pumping distribution can be spread over a larger crystal length, and this can facilitate removal of heat from the Tm:YAG rod 7.

Referring to Figure 2, a schematic diagram of the Stark energy levels of a Tm^{3+} ion in the crystal field of YAG is shown. The absorption band between the terminal laser level of the $^3\text{H}_6$ manifold and the $^3\text{H}_5$ level is centred near $1.17\mu\text{m}$, and hence the $1.064\mu\text{m}$ radiation provided by the Nd:YAG laser 2 is detuned by approximately 110nm from this absorption peak. In use of the Tm:YAG laser 1, an initial $1.064\mu\text{m}$ photon is absorbed in exciting a Tm^{3+} ion from the $^3\text{H}_6$ state to the $^3\text{H}_5$ state, and this is followed by a non-radiative relaxation of the electron into the $^3\text{F}_4$ state. The $2.02\mu\text{m}$ laser photon is produced when the Tm^{3+} ion is de-excited from a lower Stark component of the $^3\text{F}_4$ manifold to an upper Stark component of the $^3\text{H}_6$ manifold.

As this terminal laser level is quite close to the ground state of the Tm^{3+} ion, it is thermally populated at room temperature, and this hinders efficient operation of conventional Tm:YAG lasers at room temperature. As described above, conventional Tm:YAG lasers are pumped using radiation having a wavelength of around 785nm . Pumping at 785nm excites Tm^{3+} ions directly from the ground state to the $^3\text{F}_4$ state, the lasing transition then taking place from the $^3\text{F}_4$ state to the $^3\text{H}_6$ state (an upper level). Since the ground state of the $^3\text{H}_6$ manifold is close to the lasing terminal state of $^3\text{H}_6$, the thermal population decreases the population inversion and thus the gain of Tm^{3+} ions. Therefore room temperature operation is difficult. Indeed, in operation of conventional Tm:YAG lasers which are pumped by 785nm wavelength radiation, the thermal population of the $^3\text{H}_6$ state at room temperature leads to the requirement to cool the Tm:YAG lasers to substantially below room temperature.

In contrast, the present invention employs radiation having a wavelength of around $1\mu\text{m}$ to pump the Tm:YAG rod and, as described above, this leads to the excitation of Tm^{3+} ions from the $^3\text{H}_6$ state to the $^3\text{H}_5$ state, which subsequently undergo a non-radiative relaxation to the $^3\text{F}_4$ state before being de-excited back to the $^3\text{H}_6$ state to produce photons of the desired wavelength, namely around $2\mu\text{m}$.

Despite the difficulty of pumping Tm:YAG for room temperature operation, the present invention enables operation of Tm:YAG at room temperature due to the high intra-cavity density of the $1\mu\text{m}$ pumping radiation. This allows significant savings in cost and complexity to be achieved in Tm:YAG lasers embodying the present invention.

In summary, it will be appreciated that the present invention allows the construction of Tm:YAG lasers that demonstrate significant advantages over conventional Tm:YAG lasers, including low cost, high efficiency and simplicity. In particular, the positioning of a Tm:YAG rod within the resonant cavity of a Nd:YAG laser allows use of a piece of relatively inexpensive, commonly-available equipment to effectively pump a Tm:YAG laser.

In the present specification "comprises" means "includes or consists of" and "comprising" means "including or consisting of".

The features disclosed in the foregoing description, or the following claims, or the accompanying drawings, expressed in their specific forms or in terms of a means for performing the disclosed function, or a method or process for attaining the disclosed result, as appropriate, may, separately, or in any combination of such features, be utilised for realising the invention in diverse forms

thereof